

Sömlöst Rör


EN 10216-5 ADW2, ASTM-A 269, ASTM-A 312
EN 10204 3.1 / EN 10204 3.2



D mm	Gods mm	D1 mm	INCH-GAS-SCH Dimension	Kg / m	EN 1.4301	EN 1.4404	Hydraulik EN 1.4301		Hydraulik EN 1.4404	
							blankglödgat	glödgat & betat	blankglödgat	glödgat & betat
6.00	1.00	4.00		0.125	●	●	●		●	
6.00	1.50	3.00		0.169	●	●	●		●	
6.00	2.00	2.00		0.200		●				●
6.35	0.89	4.57	1/4" x 0,035"	0.122		●				●
6.35	1.24	3.87	1/4" x 0,049"	0.159		●				●
6.35	1.65	3.05	1/4" x 0,065"	0.194		●				●
8.00	1.00	6.00		0.175	●	●	●		●	
8.00	1.50	5.00		0.244	●	●	●		●	
8.00	2.00	4.00		0.300	●	●	●		●	
9.53	0.89	7.75	3/8" x 0,035"	0.193		●				●
9.53	1.24	7.05	3/8" x 0,049"	0.257		●				●
9.53	1.65	6.23	3/8" x 0,065"	0.326		●				●
10.00	1.00	8.00		0.225	●	●	●		●	
10.00	1.50	7.00		0.319	●	●	●		●	
10.00	2.00	6.00		0.401	●	●	●		●	
10.20	2.00	6.20	1/8" GAS	0.411	●	●				
12.00	1.00	10.00		0.275	●	●	●		●	
12.00	1.50	9.00		0.394	●	●	●		●	
12.00	2.00	8.00		0.501	●	●	●		●	
12.00	2.50	7.00		0.595	●	●	●		●	
12.00	3.00	6.00		0.676		●				●
12.70	0.89	10.92	1/2" x 0,035"	0.263		●				●
12.70	1.24	10.22	1/2" x 0,049"	0.356		●				●
12.70	1.65	9.40	1/2" x 0,065"	0.457		●				●
13.72	2.24	9.24	1/4" SCH 40S	0.640	●	●				
13.72	3.02	7.68	1/4" SCH 80S	0.809	●	●				
14.00	1.00	12.00		0.326	●		●			
14.00	1.50	11.00		0.470	●	●	●		●	
14.00	2.00	10.00		0.601	●	●	●		●	
15.00	1.00	13.00		0.351	●	●	●		●	
15.00	1.50	12.00		0.507	●	●	●		●	
15.00	2.00	11.00		0.651	●	●	●		●	
16.00	1.00	14.00		0.376	●	●	●		●	
16.00	1.50	13.00		0.545	●	●	●		●	
16.00	2.00	12.00		0.701	●	●	●		●	
16.00	3.00	10.00		0.977	●	●	●		●	
17.15	1.65	13.85	3/8" SCH 10S	0.640	●	●				
17.15	2.31	12.53	3/8" SCH 40S	0.858	●	●				
17.15	3.20	10.75	3/8" SCH 80S	1.118	●	●				
18.00	1.00	16.00		0.426		●				●
18.00	1.50	15.00		0.620	●	●	●		●	
18.00	2.00	14.00		0.801	●	●	●		●	
18.00	3.00	12.00		1.127		●				●
19.05	1.65	15.75	3/4" x 0,065"	0.719		●				●
19.05	2.11	14.83	3/4" x 0,083"	0.895		●				●

● =lager

Mått och ritningar är vägledande



Sömlöst Rör


EN 10216-5 ADW2, ASTM-A 269, ASTM-A 312
EN 10204 3.1 / EN 10204 3.2



D mm	Gods mm	D1 mm	INCH-GAS-SCH Dimension	Kg / m	EN 1.4301	EN 1.4404	Hydraulik EN 1.4301		Hydraulik EN 1.4404	
							blankglödgat	glödgat & betat	blankglödgat	glödgat & betat
20.00	1.00	18.00		0.476	●		●			
20.00	1.50	17.00		0.695	●	●	●		●	
20.00	2.00	16.00		0.901	●	●	●		●	
20.00	2.50	15.00		1.096	●	●	●		●	
20.00	3.00	14.00		1.277	●	●	●		●	
20.00	4.00	12.00		1.603	●		●			
20.00	5.00	10.00		1.878	●		●			
21.34	2.11	17.12	1/2" SCH 10S	1.016	●	●				
21.34	2.77	15.80	1/2" SCH 40S	1.288	●	●				
21.34	3.73	13.88	1/2" SCH 80S	1.640	●	●				
21.34	4.78	11.78	1/2" SCH 160	1.982	●	●				
21.34	7.47	6.40	1/2" SCH XXS	2.590	●					
22.00	1.50	19.00		0.770	●	●		●	●	
22.00	2.00	18.00		1.002	●	●		●	●	
22.00	3.00	16.00		1.427	●	●		●	●	
25.00	1.50	22.00		0.883	●			●		
25.00	2.00	21.00		1.152	●	●		●	●	
25.00	2.50	20.00		1.409	●	●		●	●	
25.00	3.00	19.00		1.653	●	●		●	●	
25.00	4.00	17.00		2.103		●			●	
25.40	1.65	22.10	1" x 0,065"	0.981		●			●	
26.67	2.11	22.45	3/4" SCH 10S	1.298	●	●				
26.67	2.87	20.93	3/4" SCH 40S	1.710	●	●				
26.67	3.91	18.85	3/4" SCH 80S	2.250	●	●				
26.67	5.56	15.55	3/4" SCH 160	2.939	●	●				
26.67	7.82	11.03	3/4" SCH XXS	3.740		●				
28.00	2.00	24.00		1.302	●	●		●	●	
28.00	2.50	23.00		1.596	●	●		●	●	
28.00	3.00	22.00		1.878	●	●		●	●	
28.00	4.00	20.00		2.404	●	●		●	●	
30.00	2.00	26.00		1.402	●	●		●	●	
30.00	3.00	24.00		2.028	●	●		●	●	
30.00	4.00	22.00		2.604	●	●		●	●	
33.40	2.77	27.86	1" SCH 10S	2.125	●	●				
33.40	3.38	26.64	1" SCH 40S	2.541	●	●				
33.40	4.55	24.30	1" SCH 80S	3.287	●	●				
33.40	6.35	20.70	1" SCH 160	4.350	●	●				
35.00	2.00	31.00		1.653		●			●	
35.00	3.00	29.00		2.404	●	●		●	●	
38.00	2.00	34.00		1.803	●	●		●	●	
38.00	3.00	32.00		2.629	●	●		●	●	
38.00	4.00	30.00		3.405	●	●		●	●	
38.00	5.00	28.00		4.132		●			●	
40.00	5.00	30.00		4.382	●			●		
42.00	3.00	36.00		2.930	●	●		●	●	

● =lager

Mått och ritningar är vägledande



Sömlöst Rör


EN 10216-5 ADW2, ASTM-A 269, ASTM-A 312
EN 10204 3.1 / EN 10204 3.2



D mm	Gods mm	D1 mm	INCH-GAS-SCH Dimension	Kg / m	EN 1.4301	EN 1.4404	Hydraulik EN 1.4301		Hydraulik EN 1.4404	
							blankglödgat	glödgat & betat	blankglödgat	glödgat & betat
42.16	2.77	36.62	1.1/4" SCH 10S	2,730	●	●				
42.16	3.56	35.04	1.1/4" SCH 40S	3.440	●	●				
42.16	4.85	32.46	1.1/4" SCH 80S	4.531	●	●				
42.16	6.35	29.46	1.1/4" SCH 160	5.694	●	●				
48.26	2.77	42.72	1.1/2" SCH 10S	3.160	●	●				
48.26	3.68	40.90	1.1/2" SCH 40S	4.110	●	●				
48.26	5.08	38.10	1.1/2" SCH 80S	5.500	●	●				
48.26	7.14	33.98	1.1/2" SCH 160	7.352	●	●				
48.26	10.16	27.94	1.1/2" SCH XXS	9.690		●				
48.30	4.05	40.20		4.487		●				
50.00	5.00	40.00		5.634	●	●		●		●
57.00	3.00	51.00		4.056	●	●				
57.00	6.50	47.00		6.510	●					
60.00	5.00	50.00		6.886	●	●		●		●
60.00	6.00	48.00		8.113		●				●
60.33	2.77	54.79	2" SCH 10S	3.990	●	●				
60.33	3.91	52.51	2" SCH 40S	5.520	●	●				
60.33	5.54	49.25	2" SCH 80S	7.601	●	●				
60.33	8.74	42.85	2" SCH 160	11.290	●	●				
73.03	3.05	66.93	2.1/2" SCH 10S	5.345	●	●				
73.03	5.16	62.71	2.1/2" SCH 40S	8.769	●	●				
73.03	7.01	59.01	2.1/2" SCH 80S	11.589		●				
73.03	9.53	53.97	2.1/2" SCH 160	15.153		●				
76.10	2.90	70.30		5.315	●					
76.10	3.65	68.80	2.1/2" GAS	6.535	●	●				
76.10	6.30	63.50		11.011		●				
88.90	3.05	82.80	3" SCH 10S	6.450	●	●				
88.90	4.05	80.80	3" GAS	8.605	●	●				
88.90	5.49	77.92	3" SCH 40S	11.466	●	●				
88.90	7.62	73.66	3" SCH 80S	15.509	●	●				
88.90	11.13	66.64	3" SCH 160	21.674	●	●				
101.60	3.05	95.50	3.1/2" SCH 10S	7.526	●	●				
101.60	4.05	93.50	3.1/2" GAS	9.893		●				
101.60	5.74	90.12	3.1/2" SCH 40S	13.778	●	●				
101.60	8.08	85.44	3.1/2" SCH 80S	18.921	●	●				
108.00	4.00	100.00		10.417		●				
114.30	3.05	108.20	4" SCH 10S	8.360	●	●				
114.30	4.50	105.30		12.372	●	●				
114.30	6.02	102.26	4" SCH 40S	16.322	●	●				
114.30	8.56	97.18	4" SCH 80S	22.665	●	●				
139.70	4.00	131.70		13.592		●				
141.30	3.40	134.50	5" SCH 10S	11.740	●	●				
141.30	6.55	128.20	5" SCH 40S	22.101	●	●				
141.30	9.53	122.24	5" SCH 80S	31.444	●	●				
159.00	4.50	150.00		17.409		●				

● =lager

Mått och ritningar är vägledande



Sömlöst Rör

EN 10216-5 ADW2, ASTM-A 269, ASTM-A 312
EN 10204 3.1 / EN 10204 3.2



D mm	Gods mm	D1 mm	INCH-GAS-SCH Dimension	Kg / m	EN 1.4301	EN 1.4404	Hydraulik EN 1.4301		Hydraulik EN 1.4404	
							blankglödgat	glödgat & betat	blankglödgat	glödgat & betat
168.28	3.40	161.48	6" SCH 10S	14.037	●	●				
168.28	7.11	154.06	6" SCH 40S	28.694	●	●				
168.28	10.97	146.34	6" SCH 80S	43.211	●	●				
168.30	5.00	158.30		20.445		●				
219.08	3.76	211.56	8" SCH 10S	20.272	●	●				
219.08	8.18	202.72	8" SCH 40S	43.198	●	●				
219.08	12.70	193.68	8" SCH 80S	65.630	●	●				

● =lager

Mått och ritningar är vägledande

